



	<p><b>Ref</b> 05915</p> <p><b>Machine</b> HYDRAULIC PRESS</p> <p><b>Brand</b> LOIRE</p> <p><b>Model</b> EKD 200/80</p> <p>Type Deep Drawing</p> <p>Equipped with:</p> <p>OIL HYDRAULIC CUSHION</p>
<p><b>Main Technical Data</b></p>	
<ul style="list-style-type: none"> <li>➤ Main cylinder maximum force</li> <li>➤ Return force</li> <li>➤ Usual working pressure (adjustable)</li> <li>➤ Mobile plate stroke</li> <li>➤ Max. opening plate-table (without tooling)</li> <li>➤ Table dimensions</li> <li>➤ Mobile plate dimensions</li> <li>➤ Approach fast speed</li> <li>➤ Working speed (self-adjusting)</li> <li>➤ Return fast speed</li> <li>➤ Opening between housings</li> <li>➤ Total power installed</li> </ul>	<p>200 Ton</p> <p>40 Ton</p> <p>250 kg/cm<sup>2</sup></p> <p>750 mm</p> <p>1.200 mm</p> <p>1.500 x 1.475 mm</p> <p>1.500 x 1.475 mm</p> <p>160 mm/s</p> <p>10 ÷ 30 mm/s</p> <p>50 ÷ 150 mm/s</p> <p>1.600 mm</p> <p>30 CV</p>
<p><b>LOWER OIL HYDRAULIC CUSHION:</b></p> <ul style="list-style-type: none"> <li>➤ Max. force of lower cushion</li> <li>➤ Working pressure</li> <li>➤ Lower cushion stroke</li> <li>➤ Cushion table dimensions</li> <li>➤ Cushion ascent speed</li> <li>➤ Cushion return speed</li> </ul>	<p>80 Tm</p> <p>200 kg/cm<sup>2</sup></p> <p>500 mm</p> <p>1.280 x 1.040 mm</p> <p>30 ÷ 60 mm/s</p> <p>45 ÷ 100 mm/s</p>
<p><b>Equipment:</b></p> <ul style="list-style-type: none"> <li>➤ Two-hand control device and footswitch.</li> <li>➤ Safety fences</li> <li>➤ Adapted to regulations of R.D. 1215/97.</li> </ul> <p>(characteristics based according to technical data)</p>	