



|  |                |  |
|--|----------------|--|
|  | <b>Ref</b>     | 06077  |
|  | <b>Machine</b> | PITTSBURG SEAM LOCKER  |
|  | <b>Marca</b>   | TRUMPF   |
|  | <b>Modelo</b>  | Tru Tool F 300-2   |
|  |                | For closing PITTSBURGH lock seams on straight and curved ducts |

**Main Technical Data**

|  |   |
|--|---|
|  | <ul style="list-style-type: none"> <li>➤ Voltage - Frecuency 230 V - 50-60 Hz</li> <li>➤ Material resistance 400 N/mm<sup>2</sup> 0,75 – 1,25 mm</li> <li>➤ Working speed 4 – 7 mm/min</li> <li>➤ Control idle speed n<sub>0</sub> 160/min</li> <li>➤ Nominal power consumption 500 W</li> <li>➤ Weight 5,4 kg</li> <li>➤ Min inner radius 150 mm</li> <li>➤ Min outer radius 300 mm</li> <li>➤ Protection insulation Class II</li> <li>➤ Sound level 81 dB(A9)</li> <li>➤ Hand-arm vibration less or equal to 2,5 m/s<sup>2</sup></li> </ul> |
|--|---|

➤ OTHER SPECIFICATIONS:

- Automatic adjustement to sheet thickness
- Independent procedure of bending height
- Without equipment changes for mechanize shaped or curves parts
- Results constant bending by means auto-advance
- Various application areas: Air conditioning installations, fireplaces cadding facade constructions, industrial fans ..

(Characteristics based according to technical data)