



MAHEZASA MAQUINAS – HERRAMIENTA ZARAGOZA S.A.
 Ctra. Castellón km. 4,900, T.34 976 500011 F.34 976 500174, 50013 Zaragoza (España)
 e-mail: comercial@mahezasa.es – www.mahezasa.es



Ref	06322
Machine	TRANSFORMER
Brand	ALKARGO
Model	TCA 1250 / 17.5

Main Technical Data

- | ➤ Nominal power | 1.250 KVA. | | | | | | | | | | | | | | | | | | | | | | | | |
|----------------------------------|--|-----------|---------|-----------|---------|----|--------|--|--|----|--------|--|--|----|--------|-----|-------|----|--------|--|--|----|--------|--|--|
| ➤ UNE standard | 20101 | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Year | 1996 | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Weight | 3.375 kg | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Liquid weight to | 630 kg | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Direct current voltage to 7° C | 6,05 | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Insulation level | <table border="1"> <tr> <td>50 Hz</td> <td>KV - 38</td> </tr> <tr> <td>Shock</td> <td>KV - 99</td> </tr> </table> | 50 Hz | KV - 38 | Shock | KV - 99 | | | | | | | | | | | | | | | | | | | | |
| 50 Hz | KV - 38 | | | | | | | | | | | | | | | | | | | | | | | | |
| Shock | KV - 99 | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ Low voltage | 380 V. 18.899,1 A | | | | | | | | | | | | | | | | | | | | | | | | |
| ➤ High voltage | <table border="1"> <tr> <th></th> <th></th> <th>Intensity</th> <th>KVA.</th> </tr> <tr> <td>1°</td> <td>16.800</td> <td></td> <td></td> </tr> <tr> <td>2°</td> <td>16.400</td> <td></td> <td></td> </tr> <tr> <td>3°</td> <td>16.000</td> <td>451</td> <td>1.250</td> </tr> <tr> <td>4°</td> <td>15.600</td> <td></td> <td></td> </tr> <tr> <td>5°</td> <td>15.200</td> <td></td> <td></td> </tr> </table> | | | Intensity | KVA. | 1° | 16.800 | | | 2° | 16.400 | | | 3° | 16.000 | 451 | 1.250 | 4° | 15.600 | | | 5° | 15.200 | | |
| | | Intensity | KVA. | | | | | | | | | | | | | | | | | | | | | | |
| 1° | 16.800 | | | | | | | | | | | | | | | | | | | | | | | | |
| 2° | 16.400 | | | | | | | | | | | | | | | | | | | | | | | | |
| 3° | 16.000 | 451 | 1.250 | | | | | | | | | | | | | | | | | | | | | | |
| 4° | 15.600 | | | | | | | | | | | | | | | | | | | | | | | | |
| 5° | 15.200 | | | | | | | | | | | | | | | | | | | | | | | | |

(Characteristics based according to technical data)