



	<b>Ref</b>	06673
	<b>Machine</b>	COMBINED CUTTER-BENDER MACHINE
	<b>Brand</b>	ALBA
	<b>Model</b>	COMBI 32/36

**Main Technical Data**

<b>Bending capacity:</b>						
Tensile strength		Bars number				
		Round (Ø)			Square (h)	Flat shear (60 x b)
N/mm <sup>2</sup>	P.S.I.	1	2	3	1	1
450	65.000	36	28	24	24	15
650	90.000	32	25	22	21	12
850	120.000	29	23	20	19	11
<b>Cutting capacity:</b>						
Tensile strength		Bars number				
		Round (Ø)			Square (h)	Flat shear
N/mm <sup>2</sup>	P.S.I.	1	2	3	1	1
450	65.000	32	-	-	28	35 x 23
650	90.000	29	20	16	25	35 x 19
850	120.000	25	18	14	22	35 x 14

- |                          |                    |
|--------------------------|--------------------|
| ➤ Dish speed             | 9 rpm              |
| ➤ Fuse current           | 16 A               |
| ➤ Motor power            | 3 kW               |
| ➤ Approximate net weight | 305 kg             |
| ➤ Dimensions             | 900 x 730 x 830 mm |

**Other specifications:**

- Mechanical drive by means pedal.
- Dish can turn to both work direction.
- Lower tray for tolos.
- Cut protector.

(Characteristics based according to technical data))