



| | |
|----------------|------------------------------|
| Ref | 06693 |
| Machine | UNIVERSAL MILLING MACHINE |
| Brand | MORKAIKO |
| Model | MK-2060 |
| | Equipped with: |
| | -Motor-powered ram head |
| | -3axis Fagor digital readout |

Main Technical Data

| | |
|--|------------------|
| ➤ Working surface | 2.000 x 600 mm |
| ➤ X axis (longitudinal) | 2.000 mm |
| ➤ Y axis (transversal) | 600 mm |
| ➤ T-slot number | 5 |
| ➤ T-slot distance | 80 mm |
| ➤ Table longitudinal travel | 1.500 mm |
| ➤ Table vertical travel: manual / automatic | 500 / 470 mm |
| ➤ Spindle taper | 7:24 |
| ➤ Distance nose to table | 510 / 40 mm |
| ➤ Distance nose to column | 713 / 63 mm |
| ➤ Ram transversal travel: manual / automatic | 700 / 650 m |
| ➤ Speeds number | 27 |
| ➤ Speeds range | 30 – 2.050 rpm |
| ➤ Longitudinal feed | 8.1 – 812 mm/min |
| ➤ Vertical feed | 4 – 406 mm/min |
| ➤ Ram transversal feed | 8.1 – 812 mm/min |
| ➤ Rapid longitudinal feed | 2.540 mm/min |
| ➤ Rapid vertical feed | 1.270 mm/nin |
| ➤ Rapid trasversal feed | 2.540 mm/min |
| ➤ Motor power | 12,2 kW |

(characteristics based according to technical data)