



	<b>Ref</b>	06723
	<b>Machine</b>	AUTOMATIC CAM LATHE
	<b>Brand</b>	UNAMUNO
	<b>Model</b>	TA-36
		Counterweight feeder
<b>Main Technical Data</b>		
<ul style="list-style-type: none"> <li>➤ Round capacity to</li> <li>➤ Hexagonal capacity to</li> <li>➤ Square capacity to</li> <li>➤ Head speed in continuous variation</li> <li>➤ Production in continuous variation</li> <li>➤ Pieces max length (Drilling)</li> <li>➤ Pieces max length</li> <li>➤ Workpieces number</li> <li>➤ Inner-Outer thread capacity to</li> <li>➤ Outer thread capacity with milling cutter</li> <li>➤ Drilling capacity</li> <li>➤ Lathing length</li> <li>➤ Drilling depth</li> </ul>	<ul style="list-style-type: none"> <li>36 mm</li> <li>30 mm</li> <li>24</li> <li>560-4.000 rpm</li> <li>40-1.800 pieces/hour</li> <li>140 mm</li> <li>250 mm</li> <li>6</li> <li>M-14</li> <li>M-16</li> <li>Ø 18 mm</li> <li>70 mm</li> <li>70 mm</li> </ul>	
<b>Optional equipment:</b>		
<ul style="list-style-type: none"> <li>➤ Manual and automatic feeders..</li> <li>➤ Miscellaneous devices, for knurling, turning, threading, etc.: To be agreed.</li> </ul>		

(Characteristics based according to technical data)