



<b>REF</b>	06986
<b>Machine</b>	AIRCOAT SPRAYING PUMP
<b>Brand</b>	WAGNER
<b>Model</b>	COBRA 40-10
	- High-pressure double diaphragm pump
	Equipped with: Wagner gun and hoses

### Main Technical Data

- Pump type 40 - 10
- Pump ratio 40 : 1
- Flow volume per double stroke (DH) 10 cm<sup>3</sup>
- Maximum operating pressure 25 MPa 250 bar 3.626 psi
- Maximum possible strokes in operation 200 DH/min
- Minimum air inlet pressure 0,25 MPa 2,5 bar 36,3 psi
- Maximum air inlet pressure 0,6 MPa 6 bar 87 psi
- Product temperature 1 - 80° C
- Ambient temperature 10 – 60° C
- Hydraulic oil filling amount 0,110 l
- Sound pressure level at maximum permissible air pressure 74 dB(A)

### OTHER SPECIFICATIONS:

- Processible working materials:
  - Fluid products like paints and lacquers
- Applications:
  - Water dilutable products
  - Solvent based lacquers and paints
  - Two-components coating products
  - Emulsions
  - UV lacquers
  - Primers
  - Epoxy and polyurethane lacquers
  - Liquid plastics
  - Wax based underside protection
- Typical applications
  - Furniture industry
  - Kitchen manufactures
  - Joinery
  - Construction of vehicles